

Lock Nut

| Order Coding | Model No. | Surface treatment | Max Tightening (kgf-cm) |
|--------------|------------------------------|---------------------------|-------------------------|
| RN05 | M5 x P0.5 | Black Oxide | |
| RN05_N | | Electyless Nickel Plating | |
| RN06 | M6 x P0.75 | Black Oxide | 25 |
| RN06_N | | Electyless Nickel Plating | |
| RN08 | M8 x P1.0 | Black Oxide | 50 |
| RN08_N | | Electyless Nickel Plating | |
| RN10 | M10 x P1.0 | Black Oxide | 95 |
| RN10_N | | Electyless Nickel Plating | |
| RN12 | M12 x P1.0 | Black Oxide | 140 |
| RN12_N | | Electyless Nickel Plating | |
| RN15 | M15 x P1.0 | Black Oxide | 240 |
| RN15_N | | Electyless Nickel Plating | |
| RN17 | M17 x P1.0 | Black Oxide | |
| RN17_N | | Electyless Nickel Plating | |
| RN17W | M17 x P1.0 (for WBK17-31) | Black Oxide | 550 |
| RN17W_N | | Electyless Nickel Plating | |
| RN20 | M20 x P1.0 | Black Oxide | 480 |
| RN20_N | | Electyless Nickel Plating | |
| RN20W | M20 x P1.0(for WBK17-31) | Black Oxide | 750 |
| RN20W_N | | Electyless Nickel Plating | |
| RN25 | M25 x P1.5 | Black Oxide | 860 |
| RN25_N | | Electyless Nickel Plating | |
| RN25W | M25 x P1.5(for WBK17-31) | Black Oxide | 1350 |
| RN25W_N | | Electyless Nickel Plating | |
| RN30 | M30 x P1.5 | Black Oxide | |
| RN30_N | | Electyless Nickel Plating | |
| RN30W | M30 x P1.5(for WBK17-31) | Black Oxide | 2000 |
| RN30W_N | | Electyless Nickel Plating | |
| RN35 | M35 x P1.5 | Black Oxide | |
| RN35_N | | Electyless Nickel Plating | |
| RN35W | M35 x P1.5(for WBK17-31) | Black Oxide | 3000 |
| RN35W_N | | Electyless Nickel Plating | |
| RN40 | M40 x P1.5 | Black Oxide | |
| RN40_N | | Electyless Nickel Plating | |
| RN40W | M40 x P1.5(for WBK17-31) | Black Oxide | 4000 |
| RN40W_N | | Electyless Nickel Plating | |



Black Oxide
(Fit for normal conditions)



Nickel Plating
(fit for dust-free conditions)



Black Oxide
(Fit for normal conditions)



Nickel Plating
(fit for dust-free conditions)